





ROPE SOCKET

PARVEEN Rope Sockets are used as a means to connect wireline to the tool string.


Rope Sockets are available in 4 types as under:




WEDGE TYPE



SPOOL TYPE



SLIP TYPE



CLAMP TYPE

Engineering Data for Rope Socket

SIZE (IN.)	MAX. O.D. (IN.)	F/N. O.D. (IN)	THREAD CONN. BOX (IN. TPI)	WIRE SIZE (IN)	TYPE	PART NO.
1	1.000	0.875	5/8-11 UNC	0.066-0.092	SPOOL	911000-SP
1-1/4	1.250	1.187	15/16-10 UN	0.066-0.092	SPOOL	911211-SP
1-1/2	1.500	1.375	15/16-10 UN	0.066-0.092	SPOOL	911521-SP
2-1/2	2.500	2.312	1-9/16-10 UN	0.092	SPOOL	912546-SP
1-7/8	1.750	1.875	1-1/16-10 UN	0.066-0.092	SPOOL	911932-SP
2-1/8	2.125	1.750	1-1/16-10 UN	0.092	SPOOL	912132 SP
1-1/8	1.125	0.875	5/8-11 UNC	0.066-0.092	WEDGE	911100-W
1-1/2	1.500	1.375	15/16-10 UN	0.092/0.108	WEDGE	911521-W
1-1/2	1.50	1.375	1-1/16-10 UN	0.092/0.108	WEDGE	911522-W
1-7/8	1.875	1.750	15/16-10 UN	0.092/0.108	WEDGE	911931-W
1-7/8	1.875	1.750	1-1/16-10 UN	0.092/0.108	WEDGE	911932-W
2-1/8	2.125	1.750	1-1/16-10 UN	0.092/0.108	WEDGE	912132-W
2-1/2	2.500	2.312	1-9/16-10 UN	0.092/0.108	WEDGE	912546-W
1-1/4	1.250	1.187	15/16-10 UN	0.125	CLAMP	911211-C
1-1/2	1.500	1.375	15/16-10 UN	0.125/0.187	CLAMP	911521-C
1-7/8	1.875	1.750	1-1/16-10 UN	0.187	CLAMP	911932-C
2-1/2	2.500	2.312	1-9/16-10 UN	0.250	CLAMP	912546-C
1-1/2	1.500	1.375	15/16-10 UN	0.187	SLIP	911521-SL
1-7/8	1.875	1.750	1-1/16-10 UN	0.187	SLIP	911936-SL
2-1/8	2.125	1.750	1-1/16-10 UN	0.187	SLIP	912132-SL
2-1/2	2.500	2.312	1-9/16-10 UN	0.187	SLIP	912546-SL

• Other sizes available on request