



'HB' HYDROSTATIC BAILER

PARVEEN Hydrostatic Bailer is used to clean off sand or foreign materials from around a fishing neck of tools. Hydrostatic Bailer is used in situation where Pump Type Bailer are not effective.

Engineering Data for Hydrostatic Bailer					
SIZE (IN.)	PART NO.	F/N.O.D. (IN.)	THREAD CONNECTION PIN (IN. - TPI)	GUIDE SHOE O.D.(IN.)*	GUIDE SHOE PART NO.
1.3/8	181411	1.187	15/16 - 10 UN	1.375	181411 - 13
				1.750	181721 - 17
1.3/4	181721	1.375	15/16 - 10 UN	2.156	181721 - 21
				2.687	181721 - 26

* Guide Shoe O.D. is the Max. Bailer Assembly O.D. Unless a specified O.D. is requested. The smallest O.D. Guide Shoe is supplied.


'SAB' SAND PUMP BAILER

PARVEEN Sand Pump Bailer are used when a sand bridge is encountered during operations. The bailer pulls sand into cylinder, to remove sand bridge. Bailer are available in 3 types :


1. W/ Flat Bottom : For easy bailing of sand.
2. W/ Angled Bottom : For bailing hard packed sand
3. W/ Flapper Bottom : For bailing metallic particles which can not pass thru ball & seat

Engineering Data for Sand Pump Bailer					
SIZE (IN.)	PART NO.	F/N.O.D. (IN.)	THREAD CONNECTION PIN (IN. - TPI)	GUIDE SHOE O.D.(IN.)*	GUIDE SHOE PART NO.
1.1/4	581211	1.187	15/16 - 10 UN	1.250	581211-12
				1.437	581211-14
1.5/8	581611	1.187	15/16 - 10 UN	1.850	581611-18
				2.125	581611-21
				2.500	581611-25
				2.687	581611-26
				3.500	581611-35
				3.750	581611-37

*Guide Shoe O.D. is the Max. Bailer Assembly O.D. Unless a specified O.D. is requested. The smallest O.D. Guide Shoe is supplied.



HYDROSTATIC BAILER



SAND PUMP BAILER