



CONVENTIONAL COIL TUBING STRIPPER PACKER

PARVEEN Conventional Coil Tubing Stripper / Packer is available to accommodate tubing sizes 3/4" through 2-3/8".

FEATURES/ADVANTAGES OF PARVEEN COIL TUBING STRIPPER/PACKER

- Adjustable mounting flange is suitable for 4-3/4" adjustment within the injector base.
- The union sub and nut are field interchangeable.
- Union nut can be 'latched' in up position for full visibility.
- Unique Split Clamp Cap Retainer assists field replacement of Bushing/Packer Insert.
- Piston 'Close' and 'Open' ports are 1/4" NPT and both located below the Adjustable Mounting Flange.
- Rod Wiper in Lower Bushing Gland keeps well 'trash' from seal.
- Piston Wear Ring to protect Piston Housing.
- Minimal (2-1/8") upward travel of cap-tubing Bushing-Keeper required to disassembled from Packer Housing allowing Split Cap to be located very near Injector Chains for maximum tubing support. (Upto 1-1/2" closer than competitors).
- 1/4" NPT Gage Port provides optional Injector Port.
- Double acting long stroke piston pushes Energizer/Packer Insert 3/16" beyond half length above Packer Housing for ease of change-out.
- Packer Inserts and Energizers are interchangeable with competitors. Various materials are available to suit specific well/service conditions.
- Glass-filled Teflon Non-Extrusion Ring for added support to packer elements.
- Long wearing bronze Upper and Lower Bushings.
- 1/4" NPT hydraulic and well pressure connections. No special fittings required.

