



PUMPING TEE

PARVEEN Pumping Tees are forged, which give better control on material. This versatile selection of high quality flow tees is available in a wide range of API pipe sizes and threads.

Any special combination of sizes 2" through 4", including 2" bleeders can be provided upon request. All tees come optional with a No-Corrode material.

PARVEEN Dual string pumping tees are designed for use on dual string wells having minimum tubing center to center distances. These tees can be screwed onto one string of tubing without touching the other string. 1-1/4" and 1-1/2" sizes are ideal on slim hole well hookups.



HEAVY DUTY "RED" TEES, 3000 PSI WORKING PRESSURE - 6000 PSI TEST						
ITEM NO.	BOTTOM THREAD (PLAIN OR EUE)	TOP THREAD (PLAIN OR EUE)	SIDE OUTLET (L.P.)	BLEEDER	HT.	WT. LBS.
PT-7	2"	2"	2"	1"	6"	9
PT-13	2" MALE	2"	2"	1"	7 1/4"	7
PT-8	2"	2 1/2"	2"	1"	7 1/4"	13
PT-17	2"	3"	2"	1"18"	21"	
PT-1	2"	3"	3"	1"	8"	18
PT-18	2 1/2"	2"	2"	1"	7 1/4"	13
PT-11	2 1/2"	2 1/2"	2"	1"	7 1/4"	13
PT-14	2 1/2" MALE	2 1/2"	2"-2 1/2"	1"	8"	10
PT-9	2 1/2"	2 1/2"	2 1/2"	1"	7 1/4"	12
PT-19	2 1/2"	2 1/2"	3"	1"	8"	20
PT-12	2 1/2"	3"	2"	1"	8"	20
PT-10	2 1/2"	3"	2 1/2"	1"	8"	20
PT-16	2 1/2" MALE	3"	2"	1"	8"	10
PT-2	2 1/2"	3"	3"	1"	8"	18
PT-20	3"	2 1/2"	2"	1"	8"	20
PT-21	3"	2 1/2"	2 1/2"	1"	8"	20
PT-22	3"	2 1/2"	3"	1"	8"	20
PT-23	3"	3"	2"	1"	8"	20
PT-3	3"	3"	3"	1"	8"	20
PT-25	3"MALE	3"	2"-3"	1"	9 1/2"	19
PT-4	4"	3"	3"	1"	7 3/4"	22
PT-24	4"	4"	3"	1"	7 3/4"	21
PT-6	4"	4"	4"	1"	7 3/4"	18
PST-15	1 1/2 Plain	1 1/2 Plain"	1 1/2"	1"	6"	5
PST-20	1 1/2" EUE & 2" Plain or EUE	2" Plain or EUE	2"	1"	6"	6
PST-25	2 1/2" Male or Female	2 1/2"	2"	1"	8"	12
LIGHTWEIGHT "YELLOW" TEES 2500 PSI WORKING PRESSURE - 5000 PSI TEST						
YT	2"	2"	2"	1"	5 3/4"	8"
YT	2 1/2"	2 1/2"	2 1/2"	1"	6"	9"