



TUBULARS

1. **PARVEEN** is adequately equipped to supply/thread Casings or Tubings, & Casing or Tubing Pup Joints, Casing or Tubing Connectors and Casing or Tubing Couplings. In addition it is capable of Threading items at Groups 1, 2, 3 & 4 of API spec. 5CT. Items manufactured by PARVEEN meet the Quality Standards as defined in API 5CT assuring quality manufacturing process and full material traceability. PARVEEN is licensed to Monogram these products.

2. **PARVEEN** is also well equipped to manufacture Line Pipe Couplings. In addition it can thread Line Pipes and its accessories of various sizes. Items meet the quality standards as laid down in API - 5L. PARVEEN is licensed to monogram these products.

CASING / TUBING / LINE PIPES:

PARVEEN can provide threaded Casing, Tubing, Line Pipe as per following tables:

CASING				
DIMENSIONS			THREADS	
OUTSIDE DIAMETER (IN.)	NOMINAL WEIGHT (lb/ft)	TUBE LENGTH API RANGE	API	PROPRIETARY
4.1/2	9.50 to 15.10	1, 2, 3, 4.	Short.	Can be done
5	11.50 to 24.10		Long.	On request
5.1/2	14.00 to 40.50		Buttress.	
6.5/8	20.00 to 32.00		Extreme line.	
7	17.00 to 53.60			
7.5/8	24.00 to 55.30			
7.3/4	46.10			
8.5/8	24.00 to 49.00			
9.5/8	32.30 to 75.60			
10.3/4	32.75 to 85.30			
● 13.3/8 available on request.				

TUBING					
DIMENSIONS				THREADS	
OUTSIDE DIAMETER (IN.)	NOMINAL WEIGHT (lb/ft.)	TUBE LENGTH API RANGE.	TUBE ENDS	API	PROPRIETARY
1.315	1.70 to 1.80	1, 2, 3.	External upset.	Round.	Can be done
1.660	2.30 to 3.07				on request
1.990	2.75 to 3.73		Non - upset		
2.3/8	4.00 to 7.45		Integral		
2.7/8	6.40 to 11.50		joint		
3.1/2	7.70 to 17.00				
4	9.50 to 22.00				
4.1/2	12.60 to 26.10				
● L-80, 13 Cr. Available on request.					



TUBULARS

LINE PIPE							
NOMINAL DIAMETER (IN.)	DIMENSIONS		SPECIFICATIONS	STEEL ENDS.			TUBE ENDS
	OUTSIDE DIAMETER (IN.)	NOMINAL WEIGHT (lb/ft)		API	ASTM	DIN	
1/8	0.405	0.24 to 0.31	API 5L	A25	A	St 37.0	Threaded,
1/4	0.540	0.42 to 0.54	ASTM A53		B	St. 44.0	Beveled,
3/8	0.675	0.57 to 0.74	ASTM A106	A	C	St 52.0	Square Cut.
1/2	0.840	0.85 to 1.71	DIN 1629	B		StE 210.7	
3/4	1.050	1.13 to 2.44	DIN 17172	X42		StE 240.7	
1	1.315	1.68 to 3.66	DIN 2440	X46		StE 290.7	
1.1/4	1.660	2.27 to 5.21	DIN 2441	X52		StE 320.7	
1.1/2	1.900	2.72 to 6.41		X56		StE 360.7	
2	2.3/8	2.03 to 9.03		X60		StE 385.7	
2.1/2	2.7/8	2.47 to 13.69		X65		StE 415.7	
3	3.1/2	3.03 to 18.58		X70			
3.1/2	4	3.47 to 12.50		X80			
4	4.1/2	5.84 to 27.54					
5	5.9/16	10.79 to 38.55					
6	6.5/8	12.92 to 47.06					
8	8.5/8	19.66 to 72.42					
10	10.3/4	34.24 to 104.13					
12	Available On Request.						
14	Available On Request.						